



RMC - ROBUSTO SBA



The ROBUSTOSeries Vehicle Barrier is sturdy yet elegantly designed with dual tone colour option (RAL shades) of yellow and grey that makes it stand out in bright as well as poorly lit dark environment.

The Robusto is ideal for processing vehicular traffic in and out of parking, residential complexes, commercial &office buildings etc. This vehicle barrier has at its heart a 'concealed lubricated drive' that offers several years of troublefreeperformance.

The Robustois offered with a Boom Length of 6meterstraight arm that open/close at a speed of 5 to 8secs. This barrier can also be controlled through a mobile app that is specially designed in addition to the other conventional ways (push button, wireless remote, RFID, etcetera).





















RMC - ROBUSTO SBA

DESCRIPTION	PARTICULAR
Make	Ravel Movement Control
Model	RMC-ROBUSTO-600
Material Of Construction	Electrowelded Steel (2mm)
Application	Indoor / Outdoor
Housing Dimension (in mm)	352 L X 230 W X 1065 H
Boom Arm	Extruded Aluminum profile (Dia 80 mm)
Arm Length	6 Mtrs
Arm Direction	Left / Right exchangable
Power Supply	230V AC 50/60Hz
Current	Maximum 1.6 Amps
Operating Temprature	-20°C to +70°C
Motor	24V DC
Power Consumption	250W
RPM	1700 RPM
Torque	280 Nm
Open/Close Time	5 to 8 Secs
Emergency Release	via Manual key
Communication Interface	RS-485 or TCP/IP RJ45
Ingress Protection	IP54
Duty Cycle	Intense
Operations Per Hour	140
Humidity	10 to 95%
Weight of the Product	50 Kg
Features	Mobile operating app, Wireless remote





















BOOM BARRIER

RMC - ROBUSTO SBA















